

Subdivision of T. 28 S., R. 2 W.

CHAINS

40.00 Set granite stone, 8x10x15 ins., 10 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W face, from which

A fir, 3 ins. diam., bears S.65*E., 15 lks. dist., marked $\frac{1}{4}$ S 5 B T.

A fir, 3 ins. diam., bears N.50*W., 57 lks. dist., marked $\frac{1}{4}$ S 6 B T.

65.00 House, W. M. Robinett, bears W 24 chs.

74.41 Intersect N bdy. Tp., 10 lks. E of cor. secs. 31 and 32.

(See extra pages 5478 $\frac{1}{4}$ and 5478 $\frac{1}{2}$)

Retracement and Resurvey of W. Bdy. of T. 28 S., R. 1 W. Surveyed by Fred Mensch, U. S. Cadastral Engineer Under special instructions dated June 7, 1922.

From the corner of Tps. 28 and 29 S., R. 1 W., on E bdy. of this Tp., described in notes of T. 29 S., R. 1 W., to which notes, reference is made for topography of this line, run by me, in 1922.

4.81 South, retracing the W bdy. of sec. 6, T. 29 S., R. 1 W. A point, 40.00 chs. N of the SE corner of T. 28 S., R. 2 W.; set a basalt stone, 20x10x6 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 36 only, marked $\frac{1}{4}$ S 36 on W face, from which

A hemlock, 12 ins. diam., bears S.17*W., 27 lks. dist., marked $\frac{1}{4}$ S 36 B T.

A fir, 14 ins. diam., bears N.50*W., 70 lks. dist., marked $\frac{1}{4}$ S 36 B T.

No iron post available.

39.94 From the corner of Tps. 28 and 29 S., R. 1 W. North, retracing the W. bdy. of sec. 31. Intersect the $\frac{1}{4}$ sec. cor. Fall 26 lks. W. of the cor. of secs. 25, 30, 31 and 36.

79.40

From the corner of Tps. 28 and 29 S., R. 1 W. North, on a true line, resurveying the W bdy. of sec. 31.