

County Surveyor's Record, Douglas County, Oregon

Retracement and Resurvey of W. Bdy. of T. 28 S., R. 1 W.

CHAINS	
	Over mountainous land, through heavy timber and dense undergrowth.
	Ascend 600 ft. over SE slope.
4.50	Brook, 4 lks. wide, course SE.
12.04	Same brook, course SW.
35.19	A point, 80.00 chs. N of the SE cor. of T. 28 S., R. 2 W.; set a basalt stone, 20x9x6 ins., 15 ins. in the ground, for cor. of secs. 25 and 36 only, marked S 36 on SW and S 25 on NW face, from which A fir, 20 ins. diam., bears S.21*W., 20 lks. dist., marked T 28 S R 2 W S 36 B T. A fir, 28 ins. diam., bears N.55*W., 15 lks. dist., marked T 28 S R 2 W S 25 B T. No iron post available..
39.94	The $\frac{1}{4}$ sec. cor. established for secs. 31 and 36, which is a basalt stone, 8x6x5 ins. above ground, firmly set, marked $\frac{1}{4}$ on W face. Hereafter this cor. will refer to sec. 31 only: I obliterate the marks on W face and remark the stone, $\frac{1}{4}$ S 31 on E face, from which A fir, 4 ins. diam., bears N.19*E., 32 lks. dist., marked $\frac{1}{4}$ S 31 B T: new bearing tree. A laurel, 14 ins. diam., bears S.80*E., 35 lks. dist., marked $\frac{1}{4}$ S 31 B T: old bearing tree, now dead. A fir, 36 ins. diam., bears S.39*E., 41 lks. dist., marked $\frac{1}{4}$ S 31 B T: new bearing tree. A laurel, 16 ins. diam., bears N.35*W., 25 lks. dist., I obliterate the marks on this tree. Thence, N.0*23'E. Ascend 920 ft. to
28.80	Spur, slopes E. A butte 200 ft. higher than this point, bears W about 10.00 chs. dist. Descend 300 ft. to sec. cor.
35.25	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in