

County Surveyor's Record, Douglas County, Oregon

Retracement and Resurvey of W. Bdy. of T. 28 S., R. 1 W.

CHAINS											
39.77	North, retracing the W. bdy. of sec. 30.										
79.75	Intersect the $\frac{1}{4}$ sec. cor. Fall 30 lks. W of the cor. of secs. 19, 24, 25 and 30.										

	From the corner of secs. 30 and 31.										
	North, resurveying the W bdy. of sec. 30.										
	Over mountainous land, through heavy timber and dense undergrowth.										
	Descend 480 ft. to creek.										
34.84	North Fork of Dumore Creek, 5 lks. wide, course NE.; ascend gradually.										
35.79	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 24 and 25 only, with brass cap marked										
	<table border="0"> <tr> <td>T28S</td> <td>T28S</td> </tr> <tr> <td>S24</td> <td></td> </tr> <tr> <td style="border-top: 1px solid black;">S25</td> <td>R1W</td> </tr> <tr> <td>R2W</td> <td>S30</td> </tr> <tr> <td>1923</td> <td></td> </tr> </table>	T28S	T28S	S24		S25	R1W	R2W	S30	1923	
T28S	T28S										
S24											
S25	R1W										
R2W	S30										
1923											
	from which										
	A fir, 10 ins. diam., bears S.60*W., 28 lks. dist., marked T 28 S R 2 W S 25 B T.										
	A fir, 12 ins. diam., bears N.63*W., 23 lks. dist., marked T 28 S R 2 W S 24 B T.										
39.77	The $\frac{1}{4}$ sec. cor., established for secs. 25 and 30, which is a basalt stone, 12x6x5 ins. above ground, firmly set, marked $\frac{1}{4}$ on W face. Hereafter, this corner will refer to sec. 30 only; I obliterate marks on W face of cor. stone, and mark it $\frac{1}{4}$ S 30 on E face, from which										
	A hemlock, 18 ins. diam., bears N.54*E., 43 lks. dist., marked $\frac{1}{4}$ S 30 B T: new bearing tree.										
	A fir, 12 ins. diam., bears S.20*E., 45 lks. dist., marked $\frac{1}{4}$ S 30 B T: old bearing tree.										
	A fir, 20 ins. diam., bears N.55*W., 24 lks. dist., I obliterate the marks on this old bearing tree.										