

County Surveyor's Record, Douglas County, Oregon

Retracement and Resurvey of W. Bdy. of T. 28 S., R. 1 W.

CHAINS											
	Undergrowth, rhododendron, vine maple, chinquapin and hemlock.										
40.07 80.22	North, retracing the W. bdy. of sec. 19. The $\frac{1}{4}$ sec. cor. bears E 23 lks. dist. Fall 40 lks. W of the cor. of secs. 13, 18, 19 and 24.										
	_____										
	From the cor. of secs. 19 and 30. N.0°20'E., resurveying the W bdy. of sec. 19. Over mountainous land, through heavy timber and dense undergrowth. Ascend 35 ft. to										
2.34	Spur, bears E and N.; descend 100 ft.										
14.25	Draw, opens E.; ascend 240 ft. to $\frac{1}{4}$ sec. cor.										
24.89	Brook, 4 lks. wide, course SE.										
27.12	Creek, 8 lks. wide, course SE.										
29.46	Creek, 5 lks. wide, course SE.										
36.04	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 13 and 24 only, with brass cap marked										
	<table border="0"> <tr> <td>T28S</td> <td>T28S</td> </tr> <tr> <td>S13</td> <td></td> </tr> <tr> <td>S24</td> <td>R1W</td> </tr> <tr> <td>R2W</td> <td>S19</td> </tr> <tr> <td>1923</td> <td></td> </tr> </table>	T28S	T28S	S13		S24	R1W	R2W	S19	1923	
T28S	T28S										
S13											
S24	R1W										
R2W	S19										
1923											
	from which										
	A fir, 7 ins. diam., bears S.36°W., 12 lks. dist., marked T 28 S R 2 W S 24 B T.										
	A fir, 7 ins. diam., bears N.39°W., 22 lks. dist., marked T 28 S R 2 W S 13 B T.										
38.44	Brook, 2 lks. wide, course SE.										
40.07	The $\frac{1}{4}$ sec. cor., established for secs. 19 and 24, which is a basalt stone, 12x8x5 ins. above ground, firmly set, marked $\frac{1}{4}$ on W face. Hereafter this cor. will refer to sec. 19 only. I obliterate the marks on W face of cor. stone, and mark it $\frac{1}{4}$ S 19 on E face,										