

Retracement and Resurvey of W. Bdy. of T. 28 S., R. 1 W.

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A hemlock, 10 ins. diam., bears N.66*E., 24 lks. dist., marked <math>\frac{1}{4}</math> S 19; new bearing tree.</p> <p style="padding-left: 40px;">A hemlock, 10 ins. diam., bears S.26*E., 48 lks. dist., marked <math>\frac{1}{4}</math> S 19 B T; old bearing tree.</p> <p style="padding-left: 40px;">A hemlock, 14 ins. diam., bears N.49*W., 14 lks. dist. I obliterate marks on this old bearing tree.</p> <p>Thence, N.0*15'E.</p> <p>Over broken SW slope.</p>
12.64	Spur, slopes E.; 300 ft. above $\frac{1}{4}$ sec. cor.; descend 25 ft.
17.17	Creek, 5 lks. wide, course SE.; ascend 330 ft. to sec. cor.
23.19	Brook, 3 lks. wide, course SW.
23.88	Brook, 3 lks. wide, course SW.
26.69	Brook, 3 lks. wide, course SW.
35.97	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 13, only, with brass cap marked
	$\frac{1}{4}$ S13   1923
	from which
	<p>A cedar, 7 ins. diam., bears S.41*W., 25 lks. dist. marked <math>\frac{1}{4}</math> S 13 B T.</p> <p>A fir, 28 ins. diam., bears N.27*W., 14 lks. dist., marked <math>\frac{1}{4}</math> S 13 B T.</p>
40.15	<p>The cor. established for secs. 13, 18, 19 and 24, which is a basalt stone, 8x8x4 ins. above ground, firmly set, marked with 3 notches on N and S edges. Hereafter, this cor. will refer to secs. 18 and 19 only. I mark the cor. stone, S 18 on NE., and S 19 on SE face, from which</p> <p style="padding-left: 40px;">A hemlock, 30 ins. diam., bears N.45*E., 18 lks. dist., marked T 28 S R 1 W S 18 B T; old B T.</p>