

## County Surveyor's Record, Douglas County, Oregon

Retracement and Resurvey of W. bdy. of T. 28 S., R. 1 W.

CHAINS

A fir, 40 ins. diam., bears S.55\*E., 16 lks. dist.,  
marked T 28 S R 1 W S 19 B T; old bearing tree.

A fir, 24 ins. diam., bears S.75\*W., 62 lks. dist.,  
I obliterate the marks on this old bearing tree.

A fir, 30 ins. diam., bears N.60\*W., 6 lks. dist.

I obliterate the marks on this old bearing tree.

This corner is on summit of spur, bears NW and SE.

Land, mountainous.

Soil, clay loam; 2d and 3d rate.

Timber, fir, pine, cedar and hemlock.

Undergrowth, rhododendron, vine maple, chinquapin and  
hemlock.

39.97 North, retracing the W. bdy. of sec. 18.  
79.72 The  $\frac{1}{4}$  sec. cor. bears E 12 lks. dist.  
Fall 33 lks. W of the cor. of secs. 7, 12, 13 and 18.

From the cor. of secs. 18 and 19.

N.0\*10'E., resurveying the W bdy. of sec. 18.

Over mountainous land, through heavy timber and dense  
undergrowth.

Over broken NW slope; descend 50 ft. to old  $\frac{1}{4}$  sec. cor.

22.63 Trail, from Red Butte to Deadman, bears NE and SW.

33.20 Brook, 1 link wide, course NW.

33.52 Brook, 1 link wide, course NW.

35.82 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in  
the ground, for cor. of secs. 12 and 13 only, with  
brass cap marked

T28S	T28S
S12	R1W
S13	S18
R2W	
1923	

from which

A fir, 60 ins. diam., bears S.34\*W., 52 lks. dist.,