

Retracement and Resurvey of W. Bdy. of T. 28 S., R. 1 W.

CHAINS	
	<p>marked T 28 S R 2 W S 13 B T.</p> <p>A yew, 7 ins. diam., bears N.41*W., 20 lks. dist.,</p> <p>marked T 28 S R 2 W S 12 B T.</p>
39.97	<p>The $\frac{1}{4}$ sec. cor., established for secs. 13 and 18, which is a basalt stone, 10x6x4 ins. above ground, firmly set, marked $\frac{1}{4}$ on W face. Hereafter this cor. will refer to sec. 18 only. I obliterate the marks on W face and mark the cor. stone, $\frac{1}{4}$ S 18 on E face, from which</p> <p>A hemlock, 16 ins. diam., bears N.13*E., 57 lks. dist., marked $\frac{1}{4}$ S 18 B T; new bearing tree.</p> <p>A hemlock, 24 ins. diam., bears S.18*E., 64 lks. dist., marked $\frac{1}{4}$ S 18 B T; old bearing tree.</p> <p>A fir, 12 ins. diam., bears S.70*W., 49 lks. dist.,</p> <p>I obliterate the marks on this old bearing tree</p> <p>Thence, N.0*18'E.</p> <p>Descend gradually over NW slope.</p>
12.52	Brook, 4 lks. wide, course W.
21.65	Creek, 8 lks. wide, course W.
35.85	<p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 12 only, with brass cap marked</p> <p style="text-align: center;">$\frac{1}{4}$S12 1923</p> <p style="text-align: right;">from which</p> <p>A pine, 12 ins. diam., bears S.76*W., 73 lks. dist., marked $\frac{1}{4}$ S 12 B T.</p> <p>A hemlock, 12 ins. diam., bears N.60*W., 47 lks. dist., marked $\frac{1}{4}$ S 12 B T.</p>
39.75	<p>The cor., established for secs. 7, 12, 13 and 18, which is a basalt stone, 10x6x5 ins. above ground, firmly set, marked with 4 notches on S and 2 notches on N edge. Hereafter, this cor. will refer to secs. 7 and 18 only. I mark the cor. stone, S 7 on NE and S 18 on SE face, from which</p>