

County Surveyor's Record, Douglas County, Oregon

Retracement and Resurvey of W. Bdy. of T. 28 S., R. 1 W.

CHAINS

A pine, 12 ins. diam., bears N.38°E., 37 lks. dist.,
marked T 28 S R 1 W S 7 B T; old bearing tree.

A pine, 12 ins. diam., bears S.32°E., 60 lks. dist.,
marked T 28 S R 1 W S 18 B T; old bearing tree.

A fir, 24 ins. diam., bears S.10°W., 65 lks. dist.,
I obliterate the marks on this old bearing tree.

A fir, 24 ins. diam., bears N.15°W., 59 lks. dist.,
I obliterate the marks on this old bearing tree.

Land, mountainous.

Soil, clay loam; 2d and 3d rate.

Timber, fir, hemlock, pine and cedar.

Undergrowth, rhododendron, vine maple, chinquapin and
hemlock.

39.89
79.99

North, retracing the W. bdy. of sec. 7.
The $\frac{1}{4}$ sec. cor. bears E 16 lks. dist.
Fall, 28 lks. W of the cor. of secs. 1, 6, 7 and 12.

From the cor. of secs. 7 and 18.

N.0°14'E., resurveying the W bdy. of sec. 7.

Over mountainous land, through heavy timber and dense
undergrowth.

Ascend 75 ft. over SW slope.

5.55 Spur, slopes W.; descend 150 ft. over NW slope to

17.62 Brook, 4 lks. wide, course SW.; ascend 380 ft. over SW
slope, to $\frac{1}{4}$ sec. cor.

36.10 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground, for cor. of secs. 1 and 12 only, with
brass cap marked

T28S	T28S
S 1	
S12	R1W
R2W	S7
1923	

from which

A fir, 36 ins. diam., bears S.45°W., 24 lks. dist.,