

Retracement and Resurvey of W. Bdy. of T. 28 S., R. 1 W.

CHAINS

marked T 28 S R 2 W S 12 B T.

A fir, 36 ins. diam., bears N.78*W., 11 lks. dist.,

marked T 28 S R 2 W S 1 B T.

39.89 The $\frac{1}{4}$ sec. cor., established for secs. 7 and 12, which is a basalt stone, 12x8x5 ins. above ground, firmly set, marked $\frac{1}{4}$ on W face. Hereafter this cor. will refer to sec. 7 only: I obliterate the marks on W face and mark the cor. stone, $\frac{1}{4}$ S 7 on E face, from which

A hemlock, 12 ins. diam., bears N.35*E., 34 lks. dist., marked $\frac{1}{4}$ S 7 B T; old bearing tree.

A hemlock, 6 ins. diam., bears S.55*E., 31 lks. dist., marked $\frac{1}{4}$ S 7 B T; new bearing tree.

A hemlock, 18 ins. diam., bears West, 20 lks. dist. I obliterate the marks from this old bearing tree.

Thence, N.0*10'E.

Ascend 15 feet to

2.00 Summit of spur, bears NW and SE.; descend 180 feet over NE slope to brook.

3.05 Trail from Red Butte to quartz mill, bears NW and SE.

33.02 Brook, 2 lks. wide, course SE.; ascend gradually.

36.21 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 1 only, with brass cap marked

$\frac{1}{4}$ S 1
1923

from which

A fir, 18 ins. diam., bears S.5*W., 28 lks. dist., marked $\frac{1}{4}$ S 1 B T.

A fir, 22 ins. diam., bears N.55*W., 33 lks. dist., marked $\frac{1}{4}$ S 1 B T.

40.10 The cor. established for secs. 1, 6, 7 and 12, which is a basalt stone, 10x8x4 ins. above ground, firmly