

Retracement and Resurvey of W. Bdy. of T. 28 S., R. 1 W.

CHAINS

A fir, 12 ins. diam., bears S.79\*W., 63 lks. dist., marked T 28 S R 2 W S 1 C C B T; old bearing tree.

Land, mountainous.

Soil, clay loam; 2d and 3d rate.

Timber, fir, hemlock and cedar.

Undergrowth, rhododendron, vine maple, chinquapin and hemlock.

Resurvey of South Boundary of T. 28 S., R. 2 W.  
Same Deputy and Contract.

I commence at the NE cor. of T. 29 S., R. 2 W., heretofore described (See Field Notes of T. 29 S., R. 1 W., surveyed by me, in 1922) from which, the SE cor. of T. 28 S., R. 2 W., bears East, 33.47 chs. dist.

Thence, West, resurveying the S. bdy. of sec. 36.

Note - for topography and descriptions of the corners on the following lines, see, Resurvey of N Bdy. of T. 29 S., R. 2 W., by Elmer F. Strickler, U. S. Surveyor, in 1917.

3.62 The  $\frac{1}{4}$  sec. cor., established for sec. 36, which is a basalt stone, marked and witnessed as described by the surveyor general. I destroy this corner.

6.53 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 36 only, with brass cap marked

$\frac{1}{4}$  S 36  
1923

from which

A hemlock, 14 ins. diam., bears N.20\*E., 19 lks. dist., marked  $\frac{1}{4}$  S 36 B T.

A cedar, 16 ins. diam., bears N.67\*W., 42 lks. dist., marked  $\frac{1}{4}$  S 36 B T.

40.00 The  $\frac{1}{4}$  sec. cor. of sec. 1, which is an iron post, 1 in. diam., 10 ins. above ground, marked and witnessed as described by the surveyor general.