

## County Surveyor's Record, Douglas County, Oregon

## Resurvey of South Boundary of T. 28 S., R. 2 W.

CHAINS

43.62 The cor. established for secs. 35 and 36, which is a basalt stone, marked and witnessed as described by the surveyor general. I destroy this corner.

46.53 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 35 and 36, with brass cap marked

T28S	R2 W
S35	S36
S 1	
T29SR2W	
1923	

from which

A pine, 13 ins. diam., bears N.50\*E., 69 lks. dist., marked T 28 S R 2 W S 36 B T.

A chinquapin, 12 ins. diam., bears N.71\*W., 18 lks. dist., marked T 28 S R 2 W S 35 B T.

West, resurveying the S. bdy. of sec. 35.

Note - For topography of this line, see Resurvey of N bdy. of T. 29 S., R. 2 W., by Elmer F. Strickler, U.S. Surveyor in 1917.

33.47 The corner of secs. 1 and 2, which is a stone, as described in the above noted resurvey.

37.09 The cor. established for  $\frac{1}{4}$  sec. cor. of sec. 35, which is a basalt stone, 15x8x5 ins. set, marked, and witnessed as described. I destroy this corner.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 35 only, with brass cap marked

$\frac{1}{4}$ S 35
1923

from which

A fir, 12 ins. diam., bears N.89\*E., 20 lks. dist., marked  $\frac{1}{4}$  S 35 B T.

A fir, 12 ins. diam., bears N.23\*W., 3 lks. dist., marked  $\frac{1}{4}$  S 35 B T.

73.47 The  $\frac{1}{4}$  sec. cor. of sec. 2, which is an iron post, set, marked, and witnessed as described, in the above noted