

Resurvey of South Boundary of T. 28 S., R. 2 W.

CHAINS

resurvey.

77.09 The cor. of secs. 34 and 35, which is a granite stone 8x5x5 ins. above ground, firmly set, marked and witnessed as described in the above noted resurvey.

Retracement and Resurvey of Subdivisions of
T. 28 S., R. 2 W.
Same Deputy and Contract.

N.0°3'E., retracing bet. secs. 34 and 35.

Over mountainous land, through heavy timber and dense undergrowth.

Descend 125 feet over NW slope.

3.64 Brook, 4 lks. wide, course NE.; ascend 175 feet.

15.30 Spur, slopes E.; descend 350 feet over NE slope.

31.69 Creek, 5 lks. wide, course SE.; ascend 300 feet over SE. slope.

39.80 Intersect the $\frac{1}{4}$ sec. cor., which is a lava stone, 7x6x5 ins. above ground, firmly set, marked $\frac{1}{4}$ on W face, from which

A chinquapin, 7 ins. diam., bears N.42°W., 17 lks. dist., marked $\frac{1}{4}$ S 34 B T; old bearing tree.

A pine, 18 ins. diam., bears N.50°E., 27 lks.

dist., marked $\frac{1}{4}$ S 35 B T; new bearing tree.

This $\frac{1}{4}$ sec. cor. is on summit of spur, slopes NE.

Descend 400 feet over NW slope.

57.00 Creek, 8 lks. wide, course SE.; ascend 270 feet.

68.00 Spur, slopes E.; descend 100 feet to

79.95 Intersect the cor. of secs. 26, 27, 34 and 35, which is an oak post, 12x5x5 ins. above ground, marked T 28 S S 27 on NW., and R 2 W., S 34 on SW face: I add the marks S 26 on NE., and S 35 on SE face, from which

A cedar, 14 ins. diam., bears N.83°E., 58 lks.

dist., marked T 28 S R 2 W S 26 B T; new B. T.