

County Surveyor's Record, Douglas County, Oregon

Retracement and Resurvey of Subdivisions of  
T. 28 S., R. 2 W.

CHAINS	
	<p>A fir, 28 ins. diam., bears S.9°E., 21 lks. dist., marked T 28 S R 2 W S 35 B T; new bearing tree.</p> <p>A fir, 8 ins. diam., bears S.52°W., 37 lks. dist., marked T 28 S R 2 W S 34 B T; old bearing tree.</p> <p>A laurel, 6 ins. diam., bears N.34°W., 38 lks. dist., marked T 28 S R 2 W S 27 B T; old bearing tree.</p> <p>Land, mountainous.</p> <p>Soil, clay loam; 2d rate.</p> <p>Timber, fir, pine and cedar.</p> <p>Undergrowth, rhododendron, chinquapin, live oak and vine maple.</p>
39.71	N.0°3'E., retracing bet. secs. 26 and 27.
79.47	The $\frac{1}{4}$ sec. cor. Fall 15 lks. E of the cor. of secs. 22, 23, 26 and 27.
	—————
	From the cor. of secs. 26, 27, 34 and 35.
	N.0°3'E., resurveying the E bdy. of sec. 27.
	Over mountainous land, through heavy timber and dense undergrowth.
	Descend 220 feet over NE slope to
10.30	Creek, 6 lks. wide, course SE.; ascend 180 feet to
20.00	Spur, slopes E.; continue over rolling E slope to
39.71	The $\frac{1}{4}$ sec. cor., established for secs. 26 and 27, which is a yew post, 12x4x4 ins. above ground, firmly set marked $\frac{1}{4}$ S 27 on W. Hereafter this cor. will refer to sec. 27 only. No marks are found on E face of post, from which
	<p>A fir, 18 ins. diam., bears S.41°W., 15 lks. dist., marked <math>\frac{1}{4}</math> S 27 B T; new bearing tree.</p> <p>A fir, 10 ins. diam., bears N.69°W., 14 lks. dist., marked <math>\frac{1}{4}</math> S 27 B T; old bearing tree.</p>
	Thence, N.0°10'W.
	Over broken E slope.
0.29	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in