

77
County Surveyor's Record, Douglas County, Oregon

Retracement and Resurvey of Subdivisions of
T. 28 S., R. 2 W.

CHAINS

N.0°10'W., resurveying the E bdy. of sec. 22.

Over mountainous land, through heavy timber and dense undergrowth.

0.53 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 23 and 26 only, with brass cap marked

S22	T28S S23
	S26 R2W 1923

from which

A fir, 26 ins. diam., bears N.32°E., 10 lks. dist.,
marked T 28 S R 2 W S 23 B T.

A fir, 28 ins. diam., bears S.34°E., 63 lks. dist.,
marked T 28 S R 2 W S 26 B T.

8.00 Top of ridge bears NE and SW.; descend NW slope.

9.00 Trail, Deadman to Red Butte, bears NE and SW.

17.40 Draw, opens NW.; ascend 265 feet, over SW slope.

36.00 Spur, slopes NW.; descend gradually.

39.83 The $\frac{1}{4}$ sec. cor., established for secs. 22 and 23, which is a sound fir post, 12x4x4 ins. above ground, marked $\frac{1}{4}$ S 22 on W.; and witnessed by one bearing tree. No bearing tree is found east of line as shown in the field notes. Hereafter this corner will refer to sec. 22 only; from the corner

A fir, 8 ins. diam., bears S.75°W., 10 lks.
dist., marked $\frac{1}{4}$ S 22 B T; old bearing tree.

A fir, 14 ins. diam., bears N.42°W., 10 lks.
dist., marked $\frac{1}{4}$ S 22 B T; new bearing tree.

Thence, N.0°15'W.

Descend 375 feet, over NW slope, to creek.

0.70 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 23 only, with brass cap marked