

Retracement and Resurvey of Subdivisions of
T. 28 S., R. 2 W.

CHAINS

undergrowth.

Descend 155 feet to creek.

0.89 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 14 and 23, with brass cap marked

	T28S
	S14
S15	-----
	S23
	R2W
	1923

from which

A fir, 13 ins. diam., bears N.32*E., 36 lks. dist., marked T 28 S R 2 W S 14 B T.

A hemlock, 8 ins. diam., bears S.71*E., 18 lks. dist., marked T 28 S R 2 W S 23 B T.

8.03 Cavitt Creek, 13 lks. wide, course NW.; ascend 270 feet over S W slope.

23.00 Spur, slopes SW.; descend gradually, over NW slope.

32.02 Brook, 1 lk. wide, course NW.; descend 100 feet.

39.88 The 1/4 sec. cor., established for secs. 14 and 15, which is a cedar post, 12x4x4 ins. above ground, marked 1/4 S 15 on W. Hereafter this corner will refer to sec. 15 only. No marks are found on E face of cor. post, from which

A fir, 15 ins. diam., bears S.27*W., 23 lks. dist., marked 1/4 S 15 B T; old bearing tree.

A fir, 10 ins. diam., bears N.18*W., 35 lks. dist., marked 1/4 S 15 B T; new bearing tree.

Find no trace of old bearing tree in sec. 14.

Thence, N.0*16'E.

Ascend gradually.

1.01 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor. of sec. 14 only, with brass cap marked

	1/4 S14

	1923

from which