

78
County Surveyor's Record, Douglas County, Oregon


Retracement and Resurvey of Subdivisions of
T. 28 S., R. 2 W.

CHAINS

Over mountainous land, through heavy timber and dense undergrowth.

Descend gradually along general NW slope.

0.91 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 11 and 14 only, with brass cap marked



from which

A fir, 40 ins. diam., bears N.64*E., 22 lks. dist., marked T 28 S R 2 W S 11 B T.

A cedar, 28 ins. diam., bears S.45*E., 60 lks. dist., marked T 28 S R 2 W S 14 B T.

5.14 Creek, 7 lks. wide, course W.; ascend 70 feet.

11.00 Low spur, slopes W.; descend 80 feet.

19.42 Branch of Cavitt Creek, 13 lks. wide, course W., ascend gradually to

40.16 The 1/4 sec. cor., established for secs. 10 and 11, which is a cedar post, 12x4x4 ins. above ground, firmly set, in good condition, marked 1/4 S 10 on W. Hereafter this cor. will refer to sec. 10 only. No marks are found referring to sec. 11; from the corner

A hemlock, 6 ins. diam., bears S.89*W., 16 lks. dist., marked 1/4 S 10 B T; old bearing tree.

A hemlock, 8 ins. diam., bears N.60*W., 40 lks. dist., marked 1/4 S 10 B T; new bearing tree.

Old pits and mound, not visible.

Thence; N.0*12'W.

Descend 120 feet to creek.

0.75 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor. of sec. 11 only, with brass cap marked