

Retracement and Resurvey of Subdivisions of
T. 28 S., R. 2 W.

CHAINS

1/4 S 11
1923

from which

A hemlock, 10 ins. diam., bears N.16*E., 70 lks.
dist., marked 1/4 S 11 B T.

A hemlock, 8 ins. diam., bears S.81*E., 32 lks.
dist., marked 1/4 S 11 B T.

17.52 Branch of Cavitt Creek, 16 lks. wide, course NW.; ascend
85 feet to

40.15 The cor. established for secs. 2, 3, 10 and 11, which
is a fir post, 12x4x4 ins. above ground, firmly set,
in good condition, marked T 28 S S 3 on NW and R 2 W
S 10 on SW face. No marks are found referring to
secs. 2 and 11, and hereafter this corner will refer
to secs. 3 and 10 only; from the corner

A fir, 12 ins. diam., bears S.40*W., 46 lks. dist.,
marked T 28 S R 2 W S 10 B T; old bearing tree.

A fir, 12 ins. diam., bears N.58*W., 36 lks. dist.,
marked T 28 S R 2 W S 3 B T; old bearing tree.

The original bearing tree, in sec. 2, is missing.

Land, mountainous.

Soil, clay loam; 2d and 3d rate.

Timber, fir, hemlock and cedar.

Undergrowth, rhododendron, chinquapin, vine maple and
hemlock.

N.0*3'E., resurveying the E bdy. of sec. 3.

Over mountainous land, through heavy timber and dense
undergrowth,

Descend 30 feet to creek.

0.60 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground, for cor. of secs. 2 and 11, with brass
cap marked

T28S
S 2
S3
S11
R2W
1923