

County Surveyor's Record, Douglas County, Oregon

Retracement and Resurvey of Subdivisions of
T. 28 S., R. 2 W.

CHAINS	
	<p style="text-align: right;">from which</p> <p>A fir, 6 ins. diam., bears N.77*E., 25 lks. dist., marked T 28 S R 2 W S 2 B T.</p> <p>A cedar, 10 ins. diam., bears S.72*E., 30 lks. dist., marked T 28 S R 2 W S 11 B T.</p>
1.70	Branch of Cavitt Creek, 12 lks. wide, course SW.
4.63	Creek, 10 lks. wide, course W.; ascend 700 feet over SW slope.
14.46	An old trail, bears NW and SE.
18.10	Creek, 6 lks. wide, course SW.
39.98	The $\frac{1}{4}$ sec. cor., established for secs. 2 and 3, which is a lava stone, 10x8x4 ins. above ground, firmly set, marked $\frac{1}{4}$ on W face. Hereafter, this cor. will refer to sec. 3 only. I mark the stone, $\frac{1}{4}$ S 3 on W face, from which
	<p>A fir, 24 ins. diam., bears S.84*W., 52 lks. dist., marked $\frac{1}{4}$ S 3 B T; new bearing tree.</p> <p>A fir, 12 ins. diam., bears N.53*W., 62 lks. dist., marked $\frac{1}{4}$ S 3 B T; old bearing tree.</p>
	Continue same line and measurement, over rolling land.
40.60	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 2 only, with brass cap marked
	$\frac{1}{4}$ S 2 1923
	from which
	<p>A yew, 12 ins. diam., bears N.64*E., 15 lks. dist., marked $\frac{1}{4}$ S 2 B T.</p> <p>A yew, 6 ins. diam., bears S.53*E., 19 lks. dist., marked $\frac{1}{4}$ S 2 B T.</p>
58.86	Brook, 1 lk. wide, course SE.
74.93	Intersect the closing cor. of secs. 2 and 3, on S bdy. of T. 27 S., R. 2 W., which is a cedar post, 12x4x4 ins. above ground, firmly set, marked C C T 28 S R 2 W