

Retracement and Resurvey of Subdivisions of
T. 28 S., R. 2 W.

CHAINS

on S., S 2, on E., and S 3, on W., with 2 grooves
on E and 4 grooves on W face, from which

A cedar, 7 ins. diam., bears S.51*E., 81 lks. dist.,
marked T 28 S R 2 W S 2 C C B T; old bearing
tree.

A fir, 6 ins. diam., bears S.20*W., 40 lks. dist.,
marked T 28 S R 2 W S 3 C C B T; old bearing
tree.

Angle point, at original standard corner of sections
34 and 35, of T. 27 S., R. 2 W., bears S.89*E., 167
lks. dist.

Land, mountainous and rolling.

Soil, clay loam; 3d rate.

Timber, fir, hemlock and cedar.

Undergrowth, rhododendron, chinquapin, vine maple and
hemlock.

Subdivision of T.28 S., R. 2 W.
Same Deputy and Contract


From the cor. of secs. 35 and 36, on S bdy. of Tp.
North on a Sectional Guide Meridian bet. secs. 35 and 36.
Over mountainous land, through heavy timber and dense
undergrowth.

Descend near summit of spur, to

18.00 Spur, slopes NE.; descend NW slope to

37.58 Creek, 14 lks. wide, course NE.; 800 feet lower than
sec. cor.; ascend 50 feet over SW slope to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked



from which

A fir, 13 ins. diam., bears N.72*E., 49 lks. dist.,