


County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 28 S., R. 2 W.

CHAINS

- 4.00 Spur, slopes SW.; continue to ascend, over SE slope.
- 10.75 Spur, slopes SW.; 175 feet above sec. cor.; descend 50 feet, over NW slope to
- 20.57 Brook, 3 lks. wide, course SW.; ascend 350 feet over SW. slope, to $\frac{1}{4}$ sec. cor.
- 36.67 Trail, from Deadman to Red Butte, bears NW and SE.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked




from which

A chinquapin, 14 ins. diam., bears S.31*E., 63 lks. dist., marked $\frac{1}{4}$ S 24 B T.

A chinquapin, 6 ins. diam., bears N.59*W., 11 lks. dist., marked $\frac{1}{4}$ S 23 B T.

Ascend 40 feet to

- 44.00 Top of ridge bears E and W.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 13, 14, 23 and 24 with brass cap marked



from which

A hemlock, 7 ins. diam., bears N.44*E., 27 lks. dist., marked T 28 S R 2 W S 13 B T.

A fir, 7 ins. diam., bears S.59*E., 27 lks. dist., marked T 28 S R 2 W S 24 B T.

A fir, 7 ins. diam., bears S.31*W., 21 lks. dist., marked T 28 S R 2 W S 23 B T.

A fir, 7 ins. diam., bears N.28*W., 25 lks. dist., marked T 28 S R 2 W S 14 B T.