

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 28 S., R. 2 W.

CHAINS

dist., marked T 28 S R 2 W S 12 B T.
 A fir, 40 ins. diam., bears S.39*E., 55 lks.
 dist., marked T 28 S R 2 W S 13 B T.
 A fir, 28 ins. diam., bears S.80*W., 26 lks.
 dist., marked T 28 S R 2 W S 14 B T.
 A yew, 12 ins. diam., bears N.44*W., 16 lks.
 dist., marked T 28 S R 2 W S 11 B T.

Land, mountainous.

Soil, clay loam; 2d and 3d rate.

Timber, fir, cedar, hemlock and pine.

Undergrowth, rhododendron, chinquapin, vine maple
 and hemlock.

East, on a random line, bet. secs. 12 and 13.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

81.40 Intersect E bdy. of Tp., 12 lks. N of the cor. of secs.
 12 and 13.

Thence, N.89*55'W., on a true line, bet. secs. 12 and 13.
 Over mountainous land, through heavy timber and dense
 undergrowth.

Descend 25 feet to

2.18 Brook, 1 lk. wide, course NW.; ascend 100 feet to

13.00 Spur, slopes NW.; descend 220 feet to

19.27 Creek, 5 lks. wide, course NW.; ascend gradually over
 rolling land.

40.43 Brook, 1 lk. wide, course NW.

41.40 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{r} S 12 \\ \frac{1}{4} \\ \hline S 13 \end{array}$$

1923

from which

A hemlock, 16 ins. diam., bears N.84*E., 37 lks.
 dist., marked $\frac{1}{4}$ S 12 B T.