

## Subdivisions of T. 28 S.R. 3 W.

CHAINS

A maple, 12 ins. diam., bears S.60°E., 33 lks. dist.

marked T 28 S R 3 W S 3 B T

A maple, 6 ins. diam., bears S.4°W., 29 lks dist.

marked T 28 S R 3 W S 4 B T

A Fir, 18 ins. diam., bears N.42°E., 63 lks dist.

marked T 27 S R 3 W S 33 B T

This mile is broken and rocky land, 3rd. rate.

Densely covered with forests of Fir, Cedar and Laurel.

Undergrowth thick with Vine Maple, Huckleberry, Balm,  
Hazel and Salal.

Oct 28th, 1882.

Subdivisions of T. 28 S. R. 3 W.,  
As Surveyed by William N. Gibb, Deputy Surveyor,  
under contract No. 783, dated Dec. 3, 1908.

May 23, from the cor. of Tp. 28 S., Rs. 2 and 3 W.,  
cor. heretofore described, I retrace W. on S. bdy.  
of sec. 36.

38.41 Cor. of T.29 S., Rs. 2 and 3 W., which is a stake  
marked and witnessed, as described by the Surveyor  
General. I destroy markings on this cor. referring  
to T. 28 S.

40.22 Thence W. on N. bdy. sec. 1.  
Intersect 92 lks. S. of 1/4<sup>th</sup> cor. Stake has been des-  
troyed; bearing trees standing, marked as described  
by the Surveyor General.

Set granite stone, 6 x 10 x 14 ins., 10 ins. in the  
ground for 1/4 sec. cor., marked 1/4 on N. face.

Thence W. from 1/4 sec. cor.

79.09 Cor. secs. 1,2, 35 and 36, which is a stake marked  
and witnessed as described by the Surveyor General.  
I destroy markings on this cor. referring to secs.  
35 and 36.

Thence I run East on true N. bdy. sec. 1.

38.86 1/4 sec. cor.