



Subdivisions of T. 28 S., R. 3 W.

CHAINS	<p>Thence South 88°41'E.</p>
79.09	<p>Cor. of T. 29 S., Rs. 2 and 3 W.</p> <hr/> <p>At Cor. secs. 2 and 1, T 29 S. R. 3 W., Thence I retrace West on N. bdy. sec. 2. 1/2 sec. cor. which is a stake greatly decayed, marked and witnessed as described by the Surveyor General. Set fir stake, 3 ft. long, 4 ins. sq., 24 ins. in the ground for 1/2 sec. cor., marked 1/2 on S. face.</p>
38.82	<p>Intersect 48 lks. N. of cor. secs. 2, 3, 34 and 35, which is a stake greatly decayed, marked and witnessed as described by the Surveyor General. Set cedar stake, 3 ft. long, 6 ins. sq., 24 ins. in the ground for cor. secs. 2 and 3, marked T 29 S S 2 on SE, and R 3 W S 3 on SW, face, with 4 notches on E and 2 notches on W edge. I destroy markings on bearing trees referring to secs. 34 and 35. At this cor. set off***** Thence I run North 89°18'E., on true line N. Bdy. of sec. 2.</p>
78.03	<p>1/2 sec. cor.</p>
39.21	<p>Thence East.</p>
78.03	<p>Cor secs. 1 and 2.</p> <hr/> <p>As the S. Bdy. of Tp. is out of limits in alignment, I run sectional correction line. Cor. secs. 25, 30, 31 and 36. Thence I run West on sectional correction line bet. secs. 25 and 36, through dense underbrush and heavy timber; ascend NE slope.</p>
8.95	<p>Top of Castle Rock Ridge, bears NW and SE; descend</p>