

## Subdivisions of T. 28 S. R. 3 W.

CHAINS	
	timbered, and exceptionally difficult to survey,
	At cor. secs., 25, 26, 35 and 36.
	Thence I run
	West on sectional correction line bet. secs. 26 and 35, through dense underbrush and heavy timber, ascend E. slope.
2.01	Top of ridge, bears N. and S., descend W. slope.
12.41	Creek, 8 lks. wide, flows SW., ascend E. slope.
14.80	Top of ridge, bears SW. and NE., descend W. slope.
26.30	Creek, 4 lks. wide, flows S., ascend E. slope.
37.10	Top of ridge, bears N. and S., descend W. slope.
40.00	Set granite stone, 6x12x14 ins., 10 ins. in the ground for 1/4 sec. cor., marked 1/4 on N. face, from which: A fir, 6 ins. diam., bears S.6*W., 35 lks. dist. marked 1/4 S 35 B T. An alder, 6 ins. diam., bears N.4*E., 16 lks. dist. marked 1/4 S 26 B T.
	Thence I continue West
43.00	Bottom of ravine, bears S., ascend E. slope.
54.20	Top of ridge and trail, bears N. and S., descend W. slope.
71.90	Creek, 8 lks. wide, flows S., ascend E. slope.
80.00	Set granite stone, 8x10x15 ins., 10 ins. in the ground for cor. secs., 26, 27, 34 and 35, marked with 2 notches on E. and 1 notch on S. edge, from which: A fir, 5 ins. diam., bears N.10*E., 40 lks dist. marked T 28 S R 3 W S 26 B T. A fir, 14 ins. diam., bears S.52*E., 12 lks. dist. marked T 28 S R 3 W S 35 B T. A fir, 5 ins. diam., bears S.73*W., 27 lks. dist. marked T 28 S R 3 W S 34 B T. A cedar, 5 ins. diam., bears N. 44*W., 12 lks. dist. marked T 28 S R 3 W S 27 B T.
	Land, mountainous.
	Soil, rocky, 4th grade.