

Subdivisions of T 28 S R 3 W.

CHAINS	
77.46	<p>Cor. secs. 4, 5, 32 and 33, which is a stake marked and witnessed as described by the Surveyor General.</p> <p>I destroy markings on stake and bearing trees referring to secs. 32 and 33.</p>
38.05	<p>Thence W. on North bdy. sec. 5.</p> <p>1/4 sec. cor. which is a stake greatly decayed, marked as described by the Surveyor General.</p> <p>Bearing trees have been destroyed.</p> <p>Set fir stake, 3 ft. long, 4 ins. sq., 24 ins. in the ground for 1/4 sec. cor., marked 1/4 S. on N. and S. 5 on S. face, and dig pits, 18 x 18 x 12 ins., E. and W. of cor., and raise mound of earth, 3-1/2 ft. base, 1-1/2 ft. high, S. of cor., from which:</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 10° W., 9 lks dist. marked 1/4 S 5 B T.</p> <p style="padding-left: 40px;">No other tree fit to mark.</p>
81.63	<p>Cor. secs. 5, 6, 31 and 32, which is a stake marked and witnessed as described by the Surveyor General.</p> <p>I destroy markings on this cor. and bearing trees referring to secs. 31 and 32.</p> <p style="text-align: right;">May 31, 1910</p>
10.80	<p>At cor. secs. 26, 27, 34 and 35.</p> <p>Thence I run</p> <p>West on sectional correction line bet. secs. 27 and 34, through dense underbrush and heavy timber.</p> <p>Ascend E. slope.</p> <p>Trail, bears N. and S.</p>
29.10	<p>Top of ridge, bears N. and S., descend W. slope.</p>
40.00	<p>Set fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for 1/4 sec. cor., marked 1/4 S 27 on N., and 34 on S. face; from which:</p> <p style="padding-left: 40px;">A laurel, 6 ins. diam., bears S. 45° E., 15 lks dist. marked 1/4 S 34 B T.</p>