

Subdivisions of T.28 S.R. 3 W.

CHAINS

Land mountainous, covered with dense underbrush and heavily timbered and exceptionally difficult to survey.

June 4, 1910.

At cor. secs. 29, 30, 31 and 32.

Thence I run

West on random line bet. secs. 30 and 31.

40.00 Set temp. 1/4 sec. cor.

78.93 Intersect W. bdy., 139 lks. S. of cor. secs. 25, 30, 31 and 36, which is a stake marked and witnessed as described by the Surveyor General.

Set cedar stake, 3 ft. long, 4 ins. sq., 24 ins. in the ground for closing cor. secs. 30 and 31, marked C C T 28 S R 3 W on E., S 30 on N., and S 31 on S. face, with 5 grooves on N. and 1 groove on S. face, from which:

A fir, 20 ins. diam., bears N.49*E., 52 lks dist. marked T 28 S R 3 W S 30 B T.

A fir, 24 ins. diam., bears S.80*E., 17 lks. dist. marked T 28 S R 3 W S 31 B T.

I destroy markings on other cor. and bearing trees referring to secs. 30 and 31.

Thence I run

East on true line bet. secs. 30 and 31, through dense underbrush and heavy timber, descend SE slope.

31.00 Creek, 2 lks. wide, flows SW.

38.93 Set fir stake, 3 ft. long, 4 ins. sq., 24 ins. in the ground for 1/4 sec. cor., marked 1/4 S 30 on N., and 31 on S. face, from which:

An alder, 18 ins. diam., bears N.65*W., 5 lks dist. marked 1/4 S 30 B T.

An alder, 6 ins. diam., bears S.46*W., 13 lks. dist. marked 1/4 S 31 B T.