

Subdivisions of T. 28 S R 3 W.

CHAINS

As this does not close within limits I retrace my own work without finding error.

Thence I retrace

North 89°41'E. bet. secs. 17 and 20.

39.50 1/4 sec. cor., stake greatly decayed, marked as described by the Surveyor General.

Bearing trees have been destroyed.

Set fir stake, 3 ft. long, 4 ins. sq., 24 ins. in the ground for 1/4 sec. cor., marked 1/4 S 17 on N., and 20 on S. face, from which:

A fir, 18 ins. diam., bears S., 67 lks. dist.

marked 1/4 S 20 B. T.

A cedar, 20 ins. diam., bears N.28°W., 57 lks. dist.

marked 1/4 S 17 B. T.

79.51 Cor. secs. 16, 17, 20 and 21.

June 9, 1910.

Then at point of intersection of line bet. secs. 19 and 20,

Set fir stake, 3 ft. long, 4 ins. sq., 24 ins. in the ground for closing cor. secs. 19 and 20, marked C C T 28 S R 3 W on S., S 20 on E., and S 19 on W. face, with 5 grooves on E. and 1 groove on W. face, from which:

A fir, 7 ins. diam., bears S.9°E., 35 lks. dist.

marked T 28 S R 3 W S 20 B T.

A fir, 8 ins. diam., bears S.39°W., 36 lks. dist.

marked T 28 S R 3 W S 19 B T.

Thence I run

South 4'E. on true line bet. secs. 19 and 20.

Through dense underbrush and heavy timber, ascend NE. slope.

15.90 Top of ridge, bears E. and W., descend S. slope.

35.64 Set fir stake, 3 ft. long, 4 ins. sq., 24 ins. in the ground for 1/4 sec. cor., marked 1/4 S 20 on E face,