

Subdivisions of T. 28 S R 3 W.

CHAINS	
38.50	<p>Thence from the cor. secs. 19, 24, 25 and 30, I retrace South on W. line of Sec. 30. 1/4 sec. cor., which is a stake, marked and witnessed as described by the Surveyor General.</p>
78.35	<p>Cor. secs. 25 and 36 . June 10, 1910.</p>
36.47	<p>Thence from the cor. secs. 19,24,25 and 30, I retrace North on West bdy. sec. 19. 1/4 sec. cor. which is a stake, marked and witnessed as described by the Surveyor General.</p>
76.00	<p>Cor. secs. 13,18,19 and 24 which is a stake greatly decayed, marked and witnessed as described by the Surveyor General. Set cedar stake, 3 ft. long, 4 ins. sq., 24 ins. in the ground for cor. secs. 13, 18 and 19 and 24, marked T 28 S S 18 on NE., R 3 W S 19 on SE., R 4 W S 24 on SW., and S 13 on NW. face, with 3 notches on N. and S. edges. Bearing trees as described by the Surveyor General.</p>
	<p>At point of intersection, 53 lks. N. of cor. secs. 19 24, 25 and 30, set cedar stake, 3 ft. long, 4 ins. sq., 24 ins. in the ground for closing cor. secs., 19, and 30, marked C C T 28 S R 3 W on E., S 19 on N., and S 30 on S. face, with 4 grooves on N. and 2 grooves on S. face, from which: A hemlock, 8 ins. diam., bears N.59*E., 15 lks dist. marked T 28 S R 3 W S 19 B T. A fir, 36 ins. diam., bears S.52*E., 9 lks. dist. marked T 28 S R 3 W S 30 B T. I destroy markings on other cor. and bearing trees re- ferring to secs. 19 and 30.</p>