

Subdivisions of T 28 S R 3 W.

CHAINS	
	Thence I retrace North on W. bdy. sec. 6.
40.03	Intersect 94 lks. E. of 1/4 Sec. Cor., which is a stake marked and witnessed as described by the Surveyor General.
	Thence North from 1/4 sec. cor.
81.30	Intersect 91 lks. E. of cor. T 28 S R 3 and 4 W., which is a stake marked and witnessed as described by the Surveyor General.
	Thence I run S.1*17'E. on W. bdy. sec. 6.
41.28	1/4 sec. cor.
	Thence S.1*21'E.
81.32	Cor. secs. 1 and 12.
<p>At point of intersection, 328 chs. N. 1*21'W. of cor secs. 1 and 12,</p> <p>Set cedar stake, 3 ft. long, 4 ins. sq., 24 ins. in the ground for closing cor. secs. 6 and 7, marked C C T 28 S R 3 W on E., S 6 on N., and S 7 on S. face, with 5 grooves on S. and 1 groove on N. face, from which:</p> <p>A fir, 11 ins. diam., bears N.40*E., 39 lks. dist. marked T 28 S R 3 W S 6 B T.</p> <p>A cedar, 18 ins. diam., bears S. 84*E., 24 lks. dist. marked T 28 S R 3 W S 7 B T.</p>	
	Thence I run North 89*46'E. on true line bet. secs. 6 and 7.
	<i>and</i> Ascend W. slope through dense underbrush and heavy timber.
11.00	House, Chas. Holland, bears N. 23 chs. dist.
20.20	Top of ridge, bears N. and S., descend E. slope.
38.00	Ravine, bears S., ascend W. slope.
38.63	Set cedar stake, 3 ft. long, 4 ins. sq., 24 ins. in the ground for 1/4 sec. cor., marked 1/4 S 6 on N. and 7 on S. face, from which: