

County Surveyor's Record, Douglas County, Oregon

West Boundary of T. 28 S., R. 4 W.

CHAINS			
60.00	Top of Spur descending West		+80
60.00	Commence descending		
75.00	To Dry ravine		-110
80.00	Cor. to township 28 & 29, South R. 4 & 5 W		
	Ascend in last 5 chains		+90
<p>South Boundary of T. 28 S., R. 4 W. As Surveyed By Nathaniel Ford, Deputy Surveyor, Under Contract No. 44 Dated May 30, 1854</p>			
<p><i>Wednesday July 26, 1854</i> Va. 18½* E</p>			
<p>West, on Random line on the South Boundary secs. 36, 35, 34, 33, 32 & 31., setting Temporary mile and half mile posts.</p>			
<p>West, Wednesday July 26, 1854</p>			
4/80.60	Intersect West boundary 2.50 chs., North of corner of townships 28 & 29 S. R. 4. West, therefore the correction will be 42 ² / ₃ lks. to the mile & N.89*42'E		
Va. 18*10'E			
40.60	N.89*42' on true Southern boundary of sec. 31 Set ½ sec. post at proper distance from which: A Red Fir, 4 ins. diam., bears S.18*W., 12 lks. A Maple, 6 ins. diam., bears N.55*W., 9 lks.		+35
80.60	Set a post, cor. of secs. 5, 6, 31 & 32 from which: A Dogwood, 5 ins. diam., bears S.20*E., 19 lks. dist. A Red Fir, 8 ins. diam., bears N.70*E., 13 lks. dist. A Red Fir, 18 ins. diam., bears N.20*W., 8 lks. dist. A Dogwood, 4 ins. diam., bears S.60*W., 10 lks. dist. Third rate soil, high rolling land Timber, Oak, Fir, Pine. * Under brush Oaks & Laurel		-25
Va. 18* 10' E.			
40 80.00	N.89*42' E. on true Southern boundary of sec. 32 Set ½ sec. post at proper distance from which:		+30