

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 28 S., R. 4 W.

CHAINS

40.00 Set Fir post for $\frac{1}{4}$ sec. cor. from which:
 Fir, 36 ins. diam., bears N.43*E., 114 lks.
 Fir, 8 ins. diam., bears S.40*W., 59 lks.

60.00 Top of Spur C, S.10*W.

80.00 Set Fir Post for cor. to secs. 10, 11, 14 & 15 from
 which:
 Fir, 8 ins. diam., bears N.30*E., 43 lks.
 Cedar, 30 ins. diam., bears S.40*E., 8 lks.
 Cedar, 24 ins. diam., bears S.5*W., 43 lks.
 Laurel, 18 ins. diam., bears N.88*W., 69 lks.

Land Mountainous, 3rd. rate
 Timber, scattering Fir, Pine, Oak, Laurel etc.

East, on Random line bet. secs. 11 & 14

Va. 18*E.

40.00 Set Temp. $\frac{1}{4}$ sec. cor.

80.80 Intersect N & S line 14 lks. S of cor.
 S.89*54*W., on true line bet. secs. 11 & 14

18.12 Water Ditch, C. S

21.68 Road C., N & S-- Top of Ridge

40.40 Set Yew Post for $\frac{1}{4}$ sec. cor. from which:
 Fir, 6 ins. diam. bears N.30*E., 11 lks.
 Fir, 11 ins. diam., bears S.15*E., 16 lks.

45.23 Creek, 15 lks. wide C, SW.

80.80 To Sec. Cor.
 Land Mountainous, 3rd. rate
 Timber, scattering Fir, Pine & Cedar

March 24, 1881

North, bet. secs. 10 & 11

Va. 18*E.

40.00 Set Cedar Post for $\frac{1}{4}$ sec. cor. from which:
 Fir, 30 ins. diam., bears N.20*E., 7 lks.
 Fir, 40 ins. diam., bears S.75*W., 22 lks.

40.50 Spring Branch C, SW

80.00 Set Cedar post for cor. to secs. 2, 3, 10 & 11 from