

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 28 S. R. 4 W.

CHAINS	
40.00	Set Temp. $\frac{1}{2}$ sec. cor.
80.43	Intersect line, 14 lks. N of cor. to secs. 16, 17, 20 & 21 N.89*54*W., on true line bet. secs. 17 & 20
6.50	Top of Ridge, course N & S Road
31.10	Creek, 3 lks. wide, course SW
40.21	Set Laurel Post from which: A Fir, 16 ins. diam., bears N.70*E., 17 lks. A Fir, 20 ins. diam., bears S.17*E., 37 lks.
77.18	Creek, 3 lks. wide, course South
80.43	To sec. cor. Land broken, rocky, 3rd. rate Timber, chiefly Fir, Cedar, Laurel, Oak & Pine
West, on Random line bet. secs. 18 & 19 Va. 18*30' E.	
40.00	Set Temp. $\frac{1}{4}$ sec. cor.
80.33	Intersect West boundary of township, 87 lks. S of cor. to secs. ^{18, 18 + 19, 24} 19 & 20 S.89*23'E., on true line bet. secs. ^{18 + 19} 19 & 20
40.33	Set Fir Post for $\frac{1}{4}$ sec. cor. from which: A Fir, 10 ins. diam. bears N.70*E., 250 lks. A Fir, 24 ins. diam., bears S.14*W., 60 lks.
61.70	Creek, 12 lks. wide, course South
80.33	To sec. cor. Land broken, steep rocky, 3rd. rate Timber, chiefly, scattering Fir, Cedar & Pine
North, bet. secs. 17 & 18 Va. 18* 30' E.	
40.00	Set Fir Post for $\frac{1}{4}$ sec. cor. from which: Fir, 30 ins. diam., bears N.80*E., 19 lks. Fir, 12 ins. diam., bears N.30*W., 24 lks.
42.00	Top of high round mountain