

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 28 S., R. 5 W.

CHAINS		
35.00	Leave Oak openings and enter prairie.	- 45
39.93½	Set ¼ sec. post, from which	- 75
	A Y. Oak, 15 ins. diam., bears S.86½*W., 563 lks. dist.	
	A Y. Oak, 18 ins. diam., bears N.84 ¾*W., 536 lks. dist.	
48.00	Foot of spur.	- 75
54.00	Top of spur.	+ 90
59.00	Foot of hill, N. and S.	- 100
75.00	Top of ridge and begin to descend.	+ 125
79.87	To sec. corner.	- 75
	West 25 chs. and East 45 chs. prairie, balance Oak openings, all hilly.	
	Soil, good second rate.	
<p>Note: From the course of the South Boundary of the Township and the length of the line, run North through the center. We found that the Meridian line must be short and in running East to Township Boundary between secs. 12 and 13 were satisfied the difference must be in the East Boundary of 1 or 12. We therefore chained over the East Boundary of secs. 1 and 12 and found it to be as follows:</p> <p>North on East Boundary of sec. 12.</p> <p>39.35 To ¼ sec. post.</p> <p>78.80 To corner of secs. 1, 12, 6 and 7, thence North on East Boundary of sec. 1.</p> <p>15.03 A Fir (station tree) 36 ins. diam.</p> <p>39.22 To ¼ sec. post.</p> <p>78.20 To Tp. corner (account too short 3 chs.).</p> <p>This accounts for our falling so far South in closing the Township and also in part for closing between secs. 1 and 12 and short on the North Boundary.</p>		