

County Surveyor's Record, Douglas County, Oregon

5747

X X

South Boundary of T. 28 S., R. 7 W., W. M.

CHAINS		
	<p>By Nathaniel Ford, Deputy Surveyor, under Contract No. 44, dated May 30, 1854.</p>	
	<p>East on random line on the South boundary of secs. 31, 32, 33, 34, 35 and 36, setting temporary mile and half-mile posts.</p>	
83.40	<p>Intersect East boundary, 300 lks. north of Tp. cor. The correction will be 50 lks. to the mile. Sept. 7, 1854.</p>	
	<p>Va. 18*20'E.</p>	
	<p>N.89*38½'W., on true southern boundary of sec. 36.</p>	
5.50	<p>A small stream, 10 lks. wide, course N.33*E.</p>	-30
6.25	<p>Began to ascend hill.</p>	
33.00	<p>Top of ridge bears N. and S.20*W.</p>	+150
40.00	<p>Set ¼ sec. post at proper distance, from which A B oak, 30 ins. diam., bears S.27*W., 62 lks. dist. A B oak, 12 ins. diam., bears N.33*E., 48 lks. dist.</p>	-20
80.00	<p>Set a post at proper distance, cor. of secs. 1, 2, 35, 36-50 from which A B oak, 10 ins. diam., bears S.30*W., 88 lks. dist. A B oak, 8 ins. diam., bears S.80*E., 70 lks. dist. A B oak, 7 ins. diam., bears N.57*W., 15 lks. dist. A B oak, 9 ins. diam., bears N.23*E., 21 lks. dist. Third rate soil. Timber, oak openings. Hilly land.</p>	-50
	<p>Va. 18*20'E.</p>	
	<p>N.89*38½'W., on true southern boundary of sec. 35.</p>	
40.00	<p>Set ¼ sec. post at proper distance, from which</p>	-50