

County Surveyor's Record, Douglas County, Oregon

Subdivisional lines of T. 28 S., R 7 W., W.M.

CHAINS	A B Oak, 6 ins. diam., bears N.68*W., 50 lks. dist.	
52.00	Foot of hill, bears NE and SW.	
80.00	Set a post, cor of secs. 15, 16, 21 and 22, from which	+100
	A B Oak, 24 ins. diam., bears N.45*W., 75 lks. dist.	
	A B Oak, 14 ins. diam., bears S.14*W., 32 lks. dist.	
	A B Oak, 36 ins. diam., bears N.49*E., 128 lks. dist.	
	A B Oak, 8 ins. diam., bears S.29*E., 125 lks. dist.	
	High rolling land.	
	Timber, oak openings.	
	Va. 18*30'E.	
	East on random bet. secs. 15 and 22.	
40.00	Set temp. quar. sec. post.	
80.68	Intersect E boundary, 55 lks. N of sec. cor.	
	N.89*36 $\frac{1}{2}$ *W., on true line bet. secs. 15 and 22.	
40.34	Set quar. sec. post at average dist., from which	+50
	A B Oak, 10 ins. diam., bears N.33*W., 125 lks. dist.	
	A B Oak, 18 ins. diam., bears S.27*E., 138 lks. dist.	
80.68	To sec. cor.	
	Third rate soil.	
	Timber oak openings.	
	North bet. secs. 15 and 16.	
40.00	Set quar. sec. post, from which	+50
	A B Oak, 6 ins. diam., bears N.25*E., 18 lks. dist.	
	A Laurel, 12 ins. diam., bears N.15*W., 32 lks.	