

-25-

# County Surveyor's Record, Douglas County, Oregon

5767

Subdivisional lines of T. 28 S., R 7 W., W.M.

CHAINS		
	A B Oak, 12 ins. diam., bears N.80*W., 22 lks. dist.	
80.00	Set a post, cor. of secs. 3, 4, 9 and 10, from which A B Oak, 8 ins. diam., bears S.12*E., 125 lks. dist. A B Oak, 15 ins. diam., bears S.5*W., 125 lks. dist. A W Oak, 8 ins. diam., bears N.20*W., 137 lks. dist. A B Oak, 12 ins. diam., bears N.12*E., 150 lks. dist.  Second rate soil. Timber, oak openings.	+30
	Va. 18*25'E.	
40.00	East on random bet. secs. 3 and 10. Set temp. quar. sec. post.	
80.54	Intersect E boundary at sec. cor.	
	West on true line bet. secs. 3 and 10.	
40.27	Set quar. sec. post at average dist, from which A W Oak, 12 ins. diam., bears N.85*E., 125 lks. dist. A W Oak, 10 ins. diam., bears S.85*W., 120 lks. dist.	level level
80.54	To sec. cor.  First rate soil. Level land. Timber, scattering oak.	
	North on random bet. secs. 3 and 4.	
40.00	Set temp. quar. sec. post.	
80.40	Intersect E boundary, 35 lks. E of sec. cor.	
	S.15'E on true line bet. secs. 3 and 4.	
40.40	Set quar. sec. post at proper dist, from which	level