

-29-

County Surveyor's Record, Douglas County, Oregon.

5771

Subdivisional lines of T. 28 S., R 7 W., W.M.

CHAINS	N.89*36'W., on true line bet. secs. 16 and 21.	
40.30	Set quar. sec. post at average dist., from which A B Oak, 6 ins. diam., bears N.30*W., 55 lks. dist. A B Oak, 10 ins. diam., bears S.45*E., 17 lks. dist.	-50
80.60	To sec. cor. Second rate soil. Land rolling. Timber oak openings.	
40.00	North bet. secs. 16 and 17. Set quar. sec. post, from which A B Oak, 6 ins. diam., bears S.80*W., 50 lks. dist. A W Oak, 8 ins. diam., bears S.88*W., 160 lks. dist.	+50
80.00	Set a post, cor of secs. 8, 9, 16 and 17, from which A B Oak, 7 ins. diam., bears S.63*E., 60 lks. dist. A Laurel, 15 ins. diam., bears N.65*E., 110 lks. dist. A Laurel, 18 ins. diam., bears N.35*W., 87 lks. dist. A B Oak, 18 ins. diam., bears S.60*W., 8 lks. dist. Third rate soil. High land. Timber, oak openings.	-60
40.00	Va. 18*45'E. East on random bet. secs. 9 and 16. Set temp. quar. sec. post.	
80.44	Intersect E boundary, 35 lks. N of sec. cor.	
	N.89*43'W., on true line bet. secs. 9 and 16.	