

-33-

# County Surveyor's Record, Douglas County, Oregon

5775

Subdivisional lines of T. 28 S., R 7 W., W.M.

CHAINS		
	West on random bet. secs. 30 and 31.	
40.00	Set temp. quar. sec. post.	
83.10	Intersect W boundary, 70 lks. S of sec. cor.	
	S.89*30'E., on true line bet. secs. 30 and 31.	
35.00	Entered oak openings.	level
43.10	Set quar. sec. post at proper dist., from which A B Oak, 18 ins. diam., bears S.23*E., 99 lks. dist. A B Oak, 10 ins. diam., bears N.40*E., 76 lks. dist.	
52.00	Entered prairie, bears NW and SE.	level
83.10	To sec. cor. First rate soil. Level land. Scattering oak timber.	
	North bet. secs. 29 and 30.	
40.00	Set quar. sec. post, from which A W Oak, 30 ins. diam., bears S.42*W., 118 lks. dist. A W Oak, 24 ins. diam., bears S.62*E., 78 lks. dist.	level
60.00	Began to ascend hill.	
80.00	Set a post, cor. of secs. 19, 20, 29 and 30, from which A B Oak, 15 ins. diam., bears S.26*W., 27 lks. dist. A W Oak, 12 ins. diam., bears S.26*E., 110 lks. dist. A Pine, 30 ins. diam., bears N.67*E., 23 lks. dist. A B Oak, 25 ins. diam., bears N.23*W., 29 lks. dist.	+100
	First half-mile, first rate, level land, second, third rate.	