

-35-

County Surveyor's Record, Douglas County, Oregon

5777

Subdivisional lines of T. 28 S., R 7 W., W.M.

CHAINS	<p style="text-align: center;">A B Oak, 12 ins. diam., bears S.80*W., 54 lks. dist.</p>	
52.00	A bluff of rock, 200 ft. perpendicular.	+200
80.00	Set a post, cor of secs. 17, 18, 19 and 20, from which	-250
	A Laurel, 8 ins. diam., bears S.10*W., 38 lks. dist.	
	A Maple, 12 ins. diam., bears N.45*W., 76 lks. dist.	
	A Red Fir, 40 ins. diam., bears N.23*E., 16 lks. dist.	
	A Red Fir, 20 ins. diam., bears S.73*E., 120 lks. dist.	
	Third rate land. Timber, oak, fir and pine. Underbrush, oak and laurel.	
	Va. 18*25'E.	
	East on random bet. secs. 17 and 20.	
40.00	Set temp. quar. sec. post.	
79.74	Intersect E boundary, 35 lks. S of sec. cor.	
	N.89*45'W., on true line bet. secs. 17 and 20.	+50
39.87	Set quar. sec. post at average dist., from which	
	A Maple, 3 ins. diam., bears S.80*W., 45 lks. dist.	
	A Fir, 10 ins. diam., bears N.30*W., 91 lks. dist.	
79.74	To sec. cor. Third rate soil. High hilly land. Timber, oak, fir, pine. Underbrush, oak and laurel.	
	Sept. 29, 1854.	
	West on random bet. secs. 18 and 19.	