

County Surveyor's Record, Douglas County, Oregon

Retracement S. bdy. T. 27 S., R. 7 W.
(Hathorn Survey)

CHAINS 72.66	Fall 21 lks. N. of the cor. of sec. 31 and 32, establishes by Hathorn.
	East, along the S. bdy. of sec. 32.
4.71	Offset North 6.03 chs. (Hathorn record tie); from this point the cor. established by Ford for cor. of secs. 31 and 32, bears North, 27 lks. and East 16 lks. dist.
7.60	The cor. established by Hathorn as standard cor. of secs. 5 and 6, bears North, 21 lks. dist. No evidence is found of Ford's standard cor. of secs. 5 and 6.
40.17	The $\frac{1}{4}$ sec. cor. of sec. 32 established by Hathorn, bears North 14 lks. dist. No evidence is found of the cor. established by Ford for the $\frac{1}{4}$ sec. cor. of sec. 32.
47.53	The cor. established by Hathorn for standard $\frac{1}{4}$ sec. cor. of sec. 5, bears North, 12 lks. dist. From this cor. offset North 4.40 chs. and east 3.12 chs. to Ford's standard $\frac{1}{4}$ sec. cor. of sec. 5.
80.08	Fall 20 lks. S. of Hathorn's cor. secs. 32 and 33.
	East, along the S. bdy. of sec. 33.
2.48	Offset North 3.39 chs. (Hathorn record tie); from this point the cor. established by Ford for the cor. of secs. 32 and 33, bears East, 2 lks. dist. Return to line.
7.43	Intersect the cor. established by Hathorn for standard cor. of secs. 4 and 5.
9.59	(Hathorn's tie applied to last cor.) Offset North 3.20 chs. This point is 10 lks. South and 20m lks. West of Ford's cor. of secs. 4 and 5.
39.72	The $\frac{1}{4}$ sec. cor. of sec. 33, established by Hathorn, bears North, 20 lks. dist. From this cor. I offset North 1.87 chs. and East 1.35 chs. (Hathorn record tie). This point is 6 lks. North of the cor. established by Ford for $\frac{1}{4}$ sec. cor. of sec. 33. Return to line.
47.23	The cor. established by Hathorn for standard $\frac{1}{4}$ sec. cor. of sec. 4 bears North, 30 lks. dist. No evidence is found of Ford's standard $\frac{1}{4}$ sec. cor. of sec. 4. and