

Retracement S. Bdy. T. 27 S., R. 7 W.
(Hathorn Survey)

| | |
|----------------|---|
| CHAINS 7.44 | East, along the S. bdy. of sec. 36. Make search, find no evidence of the cor. established by Hathorn for standard cor. of secs. 1 and 2. No evidence is found of Ford's standard cor. of secs. 1 and 2. |
| 40.00 | No evidence is found, after careful search, of Hathorn's $\frac{1}{4}$ sec. cor. of sec. 36. Set temp. cor. No evidence is found of Ford's $\frac{1}{4}$ sec. cor. of sec. 36. |
| 47.44 | After careful search, no evidence is found of the standard $\frac{1}{4}$ sec. cor. of sec. 1, established by Hathorn. No evidence is found of Ford's standard $\frac{1}{4}$ sec. cor. of sec. 1. |
| 79.90 | Fall 16 lks. N. of the cor. of T. 27 S., Rs. 6 and 7 W. |

Resurvey of S. Bdy. T. 27 S., R. 7 W.
(Hathorn Survey)

The cor. of T 27 S., Rs. 6 and 7 W. established by Elder and Gile in 1853, is located by record bearing and distance from the original bearing tree. This tree is now hollow with an opening at the back, through which the scribe marks are visible on the overgrowth. Cor. point falls in very old fence line.

At the exact cor. point.

Set an iron post, 3 ft. long, 3 ins. diam., 26 ins. in the ground, for cor. of T. 27 S., Rs. 6 and 7 W., with brass cap marked

| | |
|------|-----|
| T27S | |
| R7W | R6W |
| S36 | S31 |
| 1924 | |

from which (new bearing trees)

A white Oak, 14 ins. diam., bears N.84 $\frac{1}{2}$ *E., 470 lks. dist., marked T 27 S R 6 W S 31 B T.

A Black oak, 14ins. diam., bears N.86 $\frac{1}{2}$ *W., 102 lks. dist., marked T 27 S R 7 W S 36 B T.

The original bearing tree, a black oak, 40 ins. diam., bears N.85*E., 560 lks. dist.