

County Surveyor's Record, Douglas County, Oregon

Resurvey of S. Bdy. T. 27 S., R. 7 W.
(Hathorn Survey)

CHAINS

The standard cor. of T. 28 S., Rs. 6 and 7 W.,
established by Elder and Gile in 1853, hereafter
described, bears N. 89°55'E., 7.46 chas. dist.

Thence

N. 89°53'W., on S. bdy. of sec. 36.

Over nearly level land, generally open, with scattered
clumps of brush and timber, across Looking Glass Valley.

Along old fence, runs on line, orchard to North.

12.50 SW. cor. of orchard; thence grain field to North.

26.55 Pole fence, bears N.; enter brush and scattering timber.

39.95 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground, for $\frac{1}{4}$ sec. cor. of sec. 36. with brass cap

Marked

1836

1924

from which (new bearing trees)

An ash, 6 ins. diam., bears N. 53°E., 11 lks. dist.

marked $\frac{1}{4}$ S 36 B T.

An Ash, 10 ins. diam., bears N. 10 $\frac{1}{2}$ °W., 350 lks.

dist., marked $\frac{1}{4}$ S 36 B T.

Ford's standard $\frac{1}{4}$ sec. cor. of sec. 1, T. 28 S., R. 7 W.,
re-established and hereafter described, bears N. 87°10'
E., 7.50 chs. dist.

44.05 Fence, bears N.; leave timber and brush, bears N. and S.

46.65 Fence, bears N.; thence orchard to North.

61.90 Small creek, 5 lks. wide, course SW.

79.42 Wire fence, bears N. and S.; line of county road.

79.90 The point for cor. of secs. 35 and 36, at intersection
of center of county road, N. and S., with fence lines E.
and W. This is the reputed point for the cor., agrees
closely with position by proportionate measurement, and
is therefore accepted.

Cor. point in road, impracticable to set monument.

The Ford standard cor. of secs. 1 and 2, re-established
and hereafter described, bears N 86°11'E., 7.33 chs. dist.