

County Surveyor's Record, Douglas County, Oregon

Resurvey of S. Bdy. T. 27 S., R 7 W.
(Hathorn Survey)

CHAINS

available for mound. Cor. is sufficiently witnessed by the fence lines and by the corners on the Ford line.

The Ford standard $\frac{1}{4}$ sec. cor. of sec. 2, re-established and hereafter described, bears N.86*24'E., 7.31 chs. dist.

The cor. established by Ford for $\frac{1}{4}$ sec. cor. of sec. 35 re-established as angle point, hereafter described, bears N.15*W., 50 lks. dist.

From the $\frac{1}{4}$ sec. cor.

N.89*45'W., on S. bdy. of sec. 35.

Along fence line.

9.85 Wire fence, bears N.

39.88 Intersect the cor. of secs. 34 and 35, determined by the intersection of the very old rail fence lines, bearing N. and W?, to which is joined the newer fence from the E. The fence to the W. is rotten and partially removed. The point agrees closely with the position by proportionate measurement and is accepted.

At the exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 34 and 35, with brass cap
Marked

T27S	R7W
S34	S35

1924

*Fd. & Used
M 104-24
4/187 C. BAWENMAN*

from which

A wild apple tree, 5 ins.diam., bears N.88 $\frac{1}{2}$ *E., 170 lks. Dist., marked T 27 S R 7 W S 35 B T.

No bearing tree or other object available in sec.34.

No stones available for mound.

The Ford standard cor. of secs. 2 and 3, re-established and hereafter described, bears N.84*53'E., 7.30 chs. dist.

The cor. established by Ford for cor. of secs. 34 and 35 re-established as angle point, hereafter described, bears N.15*W., 76 lks. dist.