

## County Surveyor's Record, Douglas County, Oregon

//

Resurvey of S. bdy. T. 27 S., R. 7 W.  
(Hathorn survey)

CHAINS

x Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 33 and 34, with brass cap marked

T27S R7W  
AP12 S33 S34

1924

from which ( new bearing trees)

A fir, 14 ins. diam., bears N. 63°E., 33 lks. dist., marked T 27 S R 7 W S 34 B T .

A fir, 18 ins. diam., bears N. 6°W., 13 lks. dist., marked T 27 S R 7 W S 33 B T.

The original bearing tree in sec. 34, a black oak, 20 ins. diam., bears N. 46°E., 63 lks. dist.

The cor. established by Ford for cor. of secs. 33 and 34, restored as angle point, hereafter described, bears N. 32°E., 1.37 chs. dist.

Land, level in valley; remainder, hilly.

Soil, clay loam in valley, 1st rate; remainder, 2nd rate.

Timber, oak and ash in valley; remainder, second growth and scattering old growth fir.

Undergrowth, hazel, fir, oak, ash, and willow.

N. 89°38'W., on S. bdy. of sec. 33.

Over rolling mountainous land; through heavy timber and medium undergrowth.

Ascend NE. slope; 31 ft.

7.00 Top of ascent; descend NW. slope 67 ft.

11.25 Old road, bears N. and S.

12.15 Wire fence, bears N. and S.

12.26 Intersect W. bdy. Daniel Huntley D.L.C.; NW. cor. bears N. 0°05'W., 29.64 chs. dist.; SW. cor. bears S. 0°05'E., 10.28 chs. dist.

20.30 Dry draw, course N.; ascend NE. slope 21 ft.

22.65 Low spur, slopes N.; descend NW. slope 63 ft.

26.60 Old road, bears N. and S.

27.50 Foot of descent; thence level.