

County Surveyor's Record, Douglas County, Oregon

12
Resurvey of S. Bdy. T. 27 S., R. 7 W.
(Hathorn Survey)

CHAINS	
27.75	Creek, 2 lks. wide, course N., in cut, 15 ft. wide, 8 ft. deep.
28.00	Fence, bears N. and S.; leave timber and brush, same bearing.
30.00	A house, not now occupied; line cuts across NW. cor. of the house.
32.40	Intersect the cor. established by Hathorn, for the standard $\frac{1}{4}$ sec. cor. of sec. 4, located by measurement from the stumps of the original bearing trees, marks eroded by weather and decay, but identified unmistakably by position, and no other stumps or trees near. At the exact cor. point Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for angle point, with brass cap marked <p style="text-align: center;">AP 11 S33 1924</p> from which (new bearing trees) An ash, 10 ins. diam., bears N.65 $\frac{1}{2}$ *E., 350 lks. dist., marked A P B T. A white oak, 5 ins. diam., bears N.57 $\frac{1}{2}$ *W., 113 lks. dist., marked A P B T. Stump of the original SE. bearing tree, an oak, 30 ins. diam., bears S. 21*E., 372 lks. dist. Stump of original SW. bearing tree, an oak, 30 ins. diam., bears S.26*W., 250 lks. dist. The Ford standard $\frac{1}{4}$ sec. cor. of sec. 4, re-established and hereafter described, bears N.36*13'E., 1.94 chs. dist. Thence from the angle point S.89*14'W., on S. bdy. of sec. 33.
1.40	Picket fence, bears N. and S. Leave opening; enter timber and brush, bears N. and S.; ascend E, slope, 112 ft.
2.80	Pole fence, bears N. and S.
4.30	Old road, bears N. and S.
6.15	Top of ascent.