

Resurvey of S. Bdy. T. 27 S., R. 7 W.
(Hathorn Survey)

CHAINS

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for NE. cor. of sec. 5 only, with brass cap marked

AP 7
S 33

S 5
T28S
R7W

1924

from which

A fir, 18 ins. diam., bears S. 25*W., 55 lks. dist., marked T 28 S R 7 W S 5 B T.

A laurel, 10 ins. diam., bears S. 56*W., 33 lks. dist., marked T 28 S R 7 W S 5 B T.

Ford's original standard cor. of secs. 4 and 5, re-established as NW. cor. of sec. 4 only, hereafter described, bears N. 4*52'W., 3.30 chs. dist.

Thence on S. bdy. of sec. 33, and resurvey N. bdy. of sec. 5, continuing same line and measurement.

30.50 Top of ascent; thence over level bench.

32.29 Intersect the cor. established by Hathorn for standard cor. of secs. 4 and 5, located by record bearing and distance from the original SE. bearing tree, showing evidence of the old blazes, no marks found. The original SW. tree is entirely gone.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for angle point, with brass cap marked

AP 6 S33

1924

from which (new bearing trees)

A fir, 14 ins. diam., bears N. 50*E., 29 lks. dist., marked A P B T.

A fir, 14 ins. diam., bears N. 60*W., 7 lks. dist., marked A P B T.