

County Surveyor's Record, Douglas County, Oregon

16

Resurvey of S. Bdy. T. 27 S., R. 7 W.
(Hathorn Survey)

CHAINS

S.89*52'W., on S. bdy. of sec. 32, and resurvey N. bdy. of sec. 5.

Over rolling land, through heavy timber and dense undergrowth.

Descend NW. slope, 10 ft.

2.15 Dry draw, course N.; ascend NE. slope, 32 ft.

5.00 Top of small spur, slopes N.; descend NW. slope, 144 ft.

14.30 Dry draw, course N.; ascend NE. slope, 93 ft.

18.00 Top of spur, slopes N.; descend NW. slope, 55 ft.

23.50 Foot of descent on bench.

29.07 Intersect center meridional subdivision line of original sec. 5.

At this point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor. of resurvey sec. 5. with brass cap marked

1/4 S 5
1924

from which

A black oak, 10 ins. diam., bears S.66*E., 22 lks. dist., marked 1/4 S 5 B T.

A fir, 14 ins. diam., bears S.36*W., 46 lks. dist., marked 1/4 S 5 B T.

Ford's original 1/4 sec. cor. of sec. 5, restored as witness point, hereafter described, bears N.4*54'W., 4.41 chs. dist.

32.55 Intersect the cor. established by Hathorn for 1/4 sec. cor. of sec. 5, located by measurement from the original bearing trees. The SW. tree is an oak, scribe marks legible. Blazes show on SE. tree.

At the exact cor. point