

County Surveyor's Record, Douglas County, Oregon

Resurvey of S.Bdy. T. 27 S., R. 7 W.
(Hathorn Survey)

CHAINS

The cor. established by Ford for $\frac{1}{4}$ sec. cor. of sec. 32,
restored as angle point, hereafter described, bears
N.33*57'E., 5.50 chs. dist.


Thence N.89*53'W.

Descend rolling NW. slope, 208 ft.

27.55 Intersect original line bet. secs. 5 and 6.

At this point

Set an iron post, 3 ft, long, 2 ins. diam., 27 ins. in
the ground, for NW. cor. of sec. 5 only, with brass
cap marked



from which

A fir, 20 ins. diam., bears S.41*E., 50 lks, dist.,
marked T 28 S R 7 W S 5 B T.

A fir, 7 ins. diam., bears S.9*E., 37 lks. dist.,
marked T 28 S R 7 W S 5 B T.

Ford's original standard cor, of secs. 5 and 6, reestab-
lished as NE. cor. of sec. 6 only, hereafter described,
bears N.4*22'W., 5.82 chs. dist.

32.57 Intersect the cor. established by Hathorn for standard
cor. of secs. 5 and 6, located by measurement from the
original bearing trees. The SW. tree has been cut down,
marks legible on the stump. The SE. tree shows old
blazes, marks ~~over~~down.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, for angle point, with brass cap marked

AP

1924

from which

(Old bearing trees) A maple, 14 ins. diam., bears
S. 44*E., 42 lks. dist., re-marked A P B T.

(New bearing trees) A fir, 36 ins. diam., bears S.46*
W., 72 lks. dist., marked A P B T.

Thence S.88*25'W.