

Resurvey of S. Bdy. T. 27 S., R. 7 W.  
(Hathorn Survey)

CHAINS

- 3.90 Road to abandoned sawmill, bears NE. and SW.
- 4.35 Looking Glass Creek, 20 lks. wide. course NE.; ascent SE. slope, 105 ft.
- 7.60 Intersect the cor. of secs. 31 and 32, located by record bearing and distance from the original NE. fir bearing tree, marked on the bark and marks legible. The other bearing tree is not found.

At the exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 31 and 32, with brass cap marked

T27S | R7W  
S31 | S32

1924

from which (new bearing trees)

A black oak, 7 ins. diam., bears N.24\*E., 65 lks. dist., marked T 27 S R 7 W S 32 B T.

A chinquapin, 7 ins. diam., bears N.34\*W., 32 lks. dist., marked T 27 S R 7 W S 31 B T.

The original bearing tree, a fir, 40 ins. diam., bears N.2\*E., 80 lks. dist.

The cor. established by Ford for the cor. of secs. 31 and 32, restored as angle point, hereafter described, bears N.37\*42'E., 7.96 Chs. dist.

Land, mountainous.

Soil, clay loam, 2nd rate.

Timber, fir, laurel, oak, and pine.

Undergrowth, hazel, vinemaple, laurel, and fir.

N.89\*48'W., on S. Bdy. of sec. 31.

Over rolling land, through heavy timber and dense undergrowth.

- 25.90 A fence, bears NE. and SW.
- 30.00 A small shed, used as garage, on line.
- 30.50 A road, bears NE. and SW., in shallow draw, course NE.; ascend E. slope, 55 ft.