

County Surveyor's Record, Douglas County, Oregon

20

Resurvey S. Bdy. T 27 S., R. 7 W.
(Hathorn Survey)

CHAINS
32.37

Intersect the cor. established by Hathorn for standard $\frac{1}{4}$ sec. cor. of sec. 6, located by measurement from the original bearing trees, both alive and standard.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for angle point, with brass cap marked

A P

1924

from which (new bearing trees)

A white oak, 20 ins. diam., bears N.41*E., 19 lks. dist., marked A P B T.

A fir, 12 ins. diam., bears N.61*W., 48 lks. dist., marked A P B T.

Original bearing tree, an oak, 28 ins. diam., blazes open and marks plain, bears S.69*E., 52 lks. dist.

Original bearing tree, an oak, 14 ins. diam., bears S.57*W. (instead of S.56*W.), 57 lks. dist., showing old blazes.

A white oak, 20 ins. diam., county surveyor's new bearing tree, in erroneous restoration as $\frac{1}{4}$ sec. cor. of sec. 6, bears N.65*E., 82 lks. dist. marked C S $\frac{1}{4}$ S 6 T 28 S R 7 W B T.

This cor. has been used by county and local surveyors for partial subdivision of sec. 6.

Ford's standard $\frac{1}{4}$ sec. cor. of sec. 6. re-established, hereafter described, bears N.34*33'E., 8.97 chs. dist.

Thence West.

7.49 Intersect the $\frac{1}{4}$ sec. cor. of sec. 31, located by measurement from the original bearing trees, old blazes plain, but marks rotted away.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 31 only, with brass cap marked

$\frac{1}{4}$ S31

1924